



## **UPVC Ball Valves**

### **Advantages**

- Compact Design
- Excellent Flow properties
- Smooth and leak proof operation
- No Scale or Algae formation
- Weathering and Abrasion resistant
- Long working life
- Union ends for easy installation
- Excellent Chemical Resistance.

### **Specifications**

- Material: UPVC
- Operating Temperature: Up to 60°C
- Socket dimensions conforming to ISO-138 / IS-7834
- Socket thread 14 TPI. for 1/2" and 3/4" and 11 TPI. for 1" and above.

**Dimensions**

<b>OD</b>	<b>DN</b>	<b>THD</b>	<b>PN</b>	<b>L</b>	<b>H</b>	<b>E</b>	<b>B</b>	<b>Std. Pkg.</b>
<b>mm</b>	<b>mm</b>	<b>Inches</b>	<b>bar</b>	<b>mm</b>	<b>mm</b>	<b>mm</b>	<b>mm</b>	<b>Nos.</b>
20	15	1/2"	16	16	80	57	50	60
25	20	3/4"	16	19	91	69	55	30
32	25	1"	16	22	103	72	61	24
40	32	1 1/4"	16	26	117	92	92	18
50	40	1 1/2"	10	31	140	97	90	16
63	50	2"	10	38	173	124	130	12
75	65	2 1/2"	06	44	214	140	112	12
90	80	3"	06	51	240	189	157	6
110	100	4"	06	61	308	221	166	1

Available in sizes from 20mm (1/2") to 110mm (4")

PRINCE ENTERPRISE

ADD : KASTURI COMPLEX, GALA NO.K-1, ANJUR ROAD, RAHNAL VILLAGE, BHIWANDI, DISTTHANE.

PH.NO : +91-2522-271566 / 655760, TELE FAX : +91-2522-274064, MOB : 9833880999 / 9920047779